SON NON-FLAM NON-MECL CONTACT ADHESIVE

DATA SHEET Tensor



As part of our WOODWORKING range, L99N is a web spray adhesive designed for using the substrates listed above.

PRODUCT DESCRIPTION

TensorGrip[®] L99N is a completely non flammable, non methylene chloride canister adhesive. Multi purpose with excellent bond to unsanded melamine, difficult to bond foams such as memory foam and polyurethane foam and many other substrates.

ADVANTAGES

- Non-Flammable
- Non-Methylene Chloride
- High Heat Resistance
- Lowest VOC content of Non-Flam, Non-Methylene Chloride Adhesives

DIRECTIONS FOR USE

- **TensorGrip® L99N** is designed as a portable, selfcontained spray system for field or shop applications.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat. Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in 1-3 days.
- Canister system will spray adequately above 60°
 F. Canister system should be kept in warm area. In the event that the canister gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.
- Notice!!! Do not store at temperatures over 120° F.

Fully Portable System

100% Adhesive Transfer to substrate

- CANISTER STORAGE/CHANGE OVER
- If you choose to leave the hose and spray gun on the canister, leave the canister valve in the open position. Do not disconnect the hose/gun from the canister. Close and lock the spray gun. To change or disconnect canister: Turn canister valve to the off position, spray out remaining adhesive from the hose, disconnect the hose and spray gun from the canister.
- *Reconnect the hose and spray gun to a new canister of adhesive and turn the canister valve to re-pressurize. Or if you are NOT connecting to a new canister, connect hose to canister of cleaner (sold separately) and spray out until liquid is clear as the indication the hose/gun is clean.

QUIN GLOBAL US

5710 F ST, Omaha NE 68117 PH: +1 402 731 3636 | info.us@quin-global.com | www.quinglobal.com



Tensor

NON-FLAM NON-MECL CONTACT ADHESIVE

22-28%

317 g/L Clear or Blue

Long

Non-Flammable

Non-Flammable

Disposable Canister

Disposable Canister

Returnable Canister

Returnable Canister

2-4 mins dependent on temp & humidity

12 months from date of manufacture

DATA SHEET Tensor

CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

- Total Solids
- **VOC** Content
- Color
- System Flammability
- Solvent System
- Dry time
- Open time
- Shelf Life

PACKAGING

- 7L
- 22L
- 108L
- 216L

STORAGE

HANDLING & STORAGE

- Consult Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

Part Number **Canister Sizes Application Tools** Τ_

х	х	x
х	x	x
	х	x
		x
		x
х	х	x
х	х	x
х	х	x
	х	x
	<u> </u>	x x

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

JUIN

OUIN GLOBAL US

5710 F ST, Omaha NE 68117 PH: +I 402 73I 3636 | info.us@quin-global.com | www.quinglobal.com



....

Tensoryrip

SAFETY DATA SHEET L99N Tensorgrip Non-Flam Non Mecl Contact Adhesive Canister

1. Identification			
Product identifier			
Product name	L99N Tensorgrip Non-Flam Non Mecl Contact Adhesive Canister		
Product number	USA		
Recommended use of the chemical and restrictions on use			
Application	Canister Spray Adhesive		
Details of the supplier of the safety data sheet			
Supplier	Quin Global US, Inc. 5710 F St Omaha NE 68117 (402) 731 3636 (402) 731 1473 marketing.us@quin-global.com		
Emergency telephone number			
Emergency telephone	Chemtrec: 1 800 424 9300		
2. Hazard(s) identification			
Classification of the substance or mixture			
Physical hazards	Press. Gas, Compressed - H280		
Health hazards	Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 STOT SE 3 - H335		
Environmental hazards	Aquatic Chronic 3 - H412		
Human health	The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.		
Label elements			
Hazard symbols			
Signal word	Warning		
Hazard statements	 H280 Contains gas under pressure; may explode if heated. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects. 		

Precautionary statements	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 If on skin: Wash with plenty of water. P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eve irritation persists: Get medical advice/ attention.
	P337+P313 If eye irritation persists: Get medical advice/ attention.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients		
Mixtures		
Trans-1,2-DCE	30-60%	
CAS number: 156-60-5		
	40.05%	
(E)-1-Chloro-3,3,3-trifluoropropene-1	10-25%	
CAS number: 102687-65-0		

hydrocarbons

hydro carbons

4. First-aid measures			
Description of first aid measures			
General information	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.		
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.		
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.		
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.		
Eye contact	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.		
Most important symptoms and	Most important symptoms and effects, both acute and delayed		
Inhalation	May cause coughing and difficulties in breathing. May cause eye and respiratory system irritation. Overexposure may depress the central nervous system, causing dizziness and intoxication.		
Ingestion	Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.		

Skin contact	May be absorbed through the skin. Product has a defatting effect on skin. The product is irritating to eyes and skin. A single exposure may cause the following adverse effects: Dryness and/or cracking.	
Eye contact	Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.	
5. Fire-fighting measures		
Special hazards arising from the	he substance or mixture	
Specific hazards	Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up.	
Advice for firefighters		
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.	
6. Accidental release measure	S	
Personal precautions, protective equipment and emergency procedures		
Personal precautions	For personal protection, see Section 8.	
Environmental precautions		
Environmental precautions	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material.	
Methods and material for conta	ainment and cleaning up	
Methods for cleaning up	Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.	
7. Handling and storage		
Precautions for safe handling		
Usage precautions	Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use.	
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product.	
Conditions for safe storage, in	cluding any incompatibilities	
Storage precautions	Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above	

50°C/120°F

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Trans-1,2-DCE

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm Long-term exposure limit (8-hour TWA): OSHA 200 ppm OSHA = Occupational Safety and Health Administration.

Exposure controls

Protective equipment

exposures, compressed annue breathing apparatus should be used.
Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.
DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.
Use protective gloves.
Wear chemical splash goggles.
This product must not be handled in a confined space without adequate ventilation. Provide adequate general and local exhaust ventilation.

Information on basic physical and chemical properties		
Appearance	Aerosol.	
Color	Clear. Blue.	
Volatile organic compound	This product contains a maximum VOC content of 317 g/l.	
10. Stability and reactivity		
Stability	Stable at normal ambient temperatures and when used as recommended.	
Conditions to avoid	Avoid contact with the following materials: Oxidizing agents. Exposure to elevated temperatures can cause product to decompose.	
Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous gases (NOx).	
11. Toxicological information		
Information on toxicological effects		
Acute toxicity - dermal ATE dermal (mg/kg)	1,100.0	
Toxicological information on ingredients.		
	Trans-1,2-DCE	
Acute toxicity -	oral	

Acute toxicity - oral Acute toxicity oral (LD₅₀ 2,391.0 mg/kg)

	Species		Rat
	Acute toxicity - de	rmal	
	Acute toxicity dern mg/kg)	nal (LD₅₀	5,000.0
	Species		Rabbit
	ATE dermal (mg/k	(g)	5,000.0
			(E)-1-Chloro-3,3,3-trifluoropropene-1
	Skin corrosion/irritation		
	Skin corrosion/irrit	ation	Prolonged and frequent contact may cause redness and irritation.
	Serious eye dama	ge/irritatio	on
	Serious eye damage/irritation		There may be irritation and redness. The eyes may water profusely.
	Inhalation		Prolonged or repeated exposure may cause the following adverse effects: Coughing, chest tightness, feeling of chest pressure.
	Ingestion		Irritating to mouth, throat and stomach.
12. Ecological information			
13. Disposa	l considerations		
Waste treat	Waste treatment methods		
Disposal methods Dispose			of waste to licensed waste disposal site in accordance with the requirements of the ste Disposal Authority.
14. Transpo	rt information		
Air transpor	t notes	1. <75kg	, 2. <150kg
UN Number			
UN No. (TD		3500	
UN No. (ICA	AO)	3500	
UN No. (DOT) 3500		3500	
UN proper shipping name			
		Chemica	l Under Pressure, N.O.S. (Air, Compressed)
Proper shipping name (DOT) Chemica		Chemica	l Under Pressure, N.O.S. (Air, Compressed)
Transport ha	azard class(es)		
TDG class		2	
TDG label(s)	2.2	
Transport la	bels		



Packing group

SDS No.

Packing group (International) Not applicable.

15. Regulatory informatior	1
National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).
Guidance	CHIP for everyone HSG228. Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.
US Federal Regulations SARA Section 302 Extrer Present.	nely Hazardous Substances Tier II Threshold Planning Quantities
CERCLA/Superfund, Haz Present.	ardous Substances/Reportable Quantities (EPA)
SARA 313 Emission Rep Present.	orting
SARA (311/312) Hazard (Present.	Categories
•	Carcinogens and Reproductive Toxins ntain any chemicals known to the state of California to cause cancer, birth defects or any other
New Jersey "Right To Knopped Present.	ow" List
Pennsylvania "Right To K Present.	now" List
Inventories Canada - DSL/NDSL Present.	
US - TSCA Present.	
16. Other information	
Revision date	12/1/2017
Revision	5

22794

Hazard statements in full	 H280 Contains gas under pressure; may explode if heated. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.
ACA HMIS Health rating.	Moderate hazard. (2)
ACA HMIS Flammability rating.	Will not burn. (0)
ACA HMIS Physical hazard rating.	Normally stable. (0)
ACA HMIS Personal protection rating.	В
DIRECTIONS FOR USE	
PRODUCT LOGO	

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.